Product data sheet

Specifications



APC Smart-UPS RT192V RM Battery Pack 2 Rows

SURT192RMXLBP2

Overview

Lead time	Usually in Stock

Main

Number of rack unit	6U
Battery type	VRLA
Provided equipment	All required connectors Rack mounting brackets User manual

Physical

Colour	Black
Height	26.3 cm
Width	43.2 cm
Depth	73.9 cm
Net weight	181.82 kg
Mounting mode	Rack-mounted

Conformance

Standards	OSHPD

Environmental

Ambient air temperature for operation	0…40 °C
Operating altitude	0...10000 ft
Relative humidity	0…95 % non-condensing
Ambient air temperature for storage	-15…45 °C
Storage altitude	0.00…15240.00 m
Storage Relative Humidity	0…95 % non-condensing

Batteries & Runtime

Number of battery free slots	0

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Number of battery filled slots	0
Device mounting	19 inch battery tray
Battery voltage	192 V
Number of battery replacement quantity	4
Replacement battery	APCRBC140 RBC44EB SRT192BP2US SRT192RMBPUS SURT10000XLIX710 SURT192XLBP-IN

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	43.2 cm
Package 1 Width	61 cm
Package 1 Length	100.3 cm
Package 1 Weight	220.45 kg
Unit Type of Package 2	PAL
Number of Units in Package 2	4
Package 2 Height	101.4 cm
Package 2 Width	100 cm
Package 2 Length	120 cm
Package 2 Weight	879.968 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	REACh Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information
Take-back	Take-back program available

Contractual warranty

Warranty	2 years repair or replace

Recommended replacement(s)