Product data sheet

Specifications



APC Smart-UPS RT Isolation Transformer, 5000VA, 230V In/Out, 1x hard wire 3-wire (H N + E)

SURT002

Overview

Presentation	Accessory solutions to tailor the Smart-UPS to meet your specific needs.
Lead time	Usually in Stock

General

Provided equipment	Installation guide Mounting hardware User manual

Physical

Colour	Black
Depth	66 cm
Height	13 cm
Net weight	56.82 kg
Width	43.2 cm

Input

Input current limits	30 A
Load capacity	5000 VA
Network frequency	50/60 Hz
Number of input connectors	1 hard wire 3-wire (1P + N + E)
Input voltage	230 V

Output

Output connector type	Hard wire 3-wire (H N + E) 1
Output voltage	230 V

Conformance

Product certifications	C-Tick CE
Standards	EN 50091-1 EN 55022 class B EN 55024 EN 60950 EN 61000-3-2

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Environmental

Ambient air temperature for operation	0…40 °C
Relative humidity	0…95 %
Operating altitude	0...10000 ft
Ambient air temperature for storage	-25…65 °C
Storage Relative Humidity	0…95 %
Storage altitude	0.00…15240.00 m

Packing Units

Package 1 Weight	63.64 kg
Package 1 Height	34.7 cm
Package 1 width	60.3 cm
Package 1 Length	98 cm
SCC14	10731304217791
Number of Units in Package 3	6

Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	REACh Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Optimized Energy Efficiency	Energy efficient product
Take-back	Take-back program available

Contractual warranty

Warranty	2 years repair or replace