Product data sheet
Characteristics

SUA48XLBP
APC Smart-UPS XL 48V Battery Pack Tower/ Rack Convertible



Overview

Lead time	Usually Ships within 2 Weeks

General

Provided equipment	User Manual

Physical

Number of rack unit	5U
Color	Black
Depth	19.49 in (49.5 cm)
Height	17.48 in (44.4 cm)
Net Weight	146.30 lb(US) (66.36 kg)
Maximum Width	8.70 in (22.1 cm)

Input

Nominal Input Voltage	DC

Environmental

Ambient air temperature for operation	32…104 °F (0…40 °C)
Relative humidity	0…95 %
Operating altitude	0...10000 ft
Ambient air temperature for storage	5…113 °F (-15…45 °C)
Storage altitude	0…50000 ft (0.00…15240.00 m)

Batteries & Runtime

Battery type	Lead-Acid battery
Included Battery Modules	0
Battery Slots Empty	0
RBC Quantity	2
Additional information	For use with "SUA" 2200/3000VA 5U rack/tower models. Can be used with 3U models with SUA039 extension cable.
Liquid Electrolyte Value	0

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein.
This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.
It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof.
Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Ordering and shipping details

GTIN	00731304244301
Package weight(Lbs)	167.33 lb(US) (75.9 kg)

Packing Units

Package 1 Height	22.01 in (55.9 cm)
Package 1 width	15.00 in (38.1 cm)
Package 1 Length	30.00 in (76.2 cm)
Number of Units in Package 3	2

Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	REACh Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information

Contractual warranty

Warranty	2 years repair or replace