Product datasheet

Specifications



Easy UPS 3S Battery Breaker Kit

E3SOPT008

Overview

Presentation	Battery breaker kit that controls DC voltage sent from third party battery solutions to the UPS. For use with the Easy UPS 3S empty battery cabinet (E3SEBC7).
Lead time	Usually Ships within 6 Weeks

Main

Battery type	VRLA

Batteries & Runtime

Number of battery filled slots	0
Number of battery free slots	0

Physical

Height	43 cm
Width	27 cm
Depth	24 cm
Net weight	8 kg

Environmental

Ambient air temperature for operation	0…40 °C
Relative humidity	0…95 % non-condensing
Operating altitude	0...3333 ft
Ambient air temperature for storage	-15…40 °C
Storage Relative Humidity	0…95 % non-condensing
Storage altitude	0.00…15240.00 m

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	43 cm
Package 1 Width	24 cm

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Package 1 Length	27 cm
Package 1 Weight	8 kg

Offer Sustainability

REACh Regulation	REACh Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
RoHS exemption information	Yes
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Recommended replacement(s)