Product data sheet

Specifications



Easy UPS 3S Battery String

E3SBT4

Overview

Presentation	Battery string for use with Easy UPS 3S with internal battery slots and Easy UPS 3S Empty Modular Battery Cabinet (E3SXR6). Each battery string consists of four 7.2 Ah battery modules.
Lead time	Usually Ships within 6 Weeks

Main

Battery type	VRLA

Batteries & Runtime

Number of battery free slots	0
Number of battery filled slots	0
Device mounting	Enclosed battery cartridge
Battery power in VAh	0 VAh

Physical

Height	15.7 cm
Width	42.8 cm
Depth	76 cm
Net weight	108 kg
Mounting mode	Not rack-mountable

Environmental

Ambient air temperature for operation	0…40 °C
Operating altitude	0...3281 ft
Relative humidity	0…95 % non-condensing
Ambient air temperature for storage	-15…40 °C
Storage altitude	0.00…15240.00 m
Storage Relative Humidity	0…95 % non-condensing

Packing Units

Unit Type of Package 1	PCE

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Number of Units in Package 1	1
Package 1 Height	18.000 cm
Package 1 Width	60.000 cm
Package 1 Length	82.000 cm
Package 1 Weight	137.000 kg

Offer Sustainability

REACh Regulation	REACh Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
China RoHS Regulation	China RoHS declaration
RoHS exemption information	Yes
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Contractual warranty

Warranty	1 year repair or replace

Recommended replacement(s)