Ürün Özellikleri

Eaton ELP1600FR

Catalog Number: ELP1600FR

Eaton Ellipse PRO UPS FR, 1600 VA, 1000 W, Input: C14, Outputs: (4) French, (4) French surge only, Tower

General specifications

Product Name	**Catalog Number**
Eaton Ellipse PRO UPS	ELP1600FR
Product Length/Depth	**Product Height**
82 mm	275 mm
Product Width	**Product Weight**
390 mm	11.3 kg
Compliances	**Certifications**
CE Marked	IEC/EN 62040-1 IEC/EN 62040-2 CE EAC

Ürün Özellikleri

Secondary frequency - max

60 Hz

Wattage

1000 W

Output power factor

0.6

Form factor

Tower

Includes network card

No

Input connection

Protective contact (SCHUKO)

Input voltage - min

150 V

Output voltage - max

284 V

Secondary frequency - min

50 Hz

Software compatibility

Eaton UPS Companion (enables safe system shutdown, energy usage metering and configuration of UPS settings)

Battery replacement

User replaceable

Battery type

Sealed, lead-acid

Efficiency

97

Special features

Convenient extra-flat design for easy installation in any office environment
Automatic Voltage Regulation (AVR)
High performance surge-protection device compliant with IEC 61643-11 standard
Data line protection to ensure that the internet line (including xDSL) is protected against surges
LCD display for real-time status and measurements
8 outlets to connect your PC + peripherals
EcoControl function helps you save up to 20 % energy compared

Kaynaklar

User guides

Eaton Ellipse PRO UPS 650/800/1200/1600 VA Installation and user manual (multiple languages)

to previous generation UPSs
HID-compliant USB port (cable supplied), for automatic integration with major operating systems (Windows/Mac OS/Linux)
Easy to replace battery helps to extend UPS service life

Construction type

Free standing model

Output voltage - min

176 V

Color

Black

Extended battery capability

No

Output voltage range

176-284 V

Topology

Line-interactive

Surge protection

Yes

Runtime at half load

9 min

Input nominal voltage

230V default (220/230/240V)

Input frequency range

46-70 Hz

Input voltage - max

285 V

Voltage type

AC

Phase (output)

1

Battery management

Replaceable batteries, Automatic battery test, deep-discharge protection, cold-start capable

Auto shutdown function

Yes

Operating temperature - min

0 °C

VA rating

1600 VA

Potential free switch contact

No

Receptacle

(4) French, (4) French surge only

Phase (input)

1

Package contents

Input cable

USB cable

User manual

Safety instructions

Noise level

<27 dB at 1 meter

Feed type

1

Runtime graph

View runtime graph

User interface

LCD (UPS status and measurements, configuration of UPS settings)

Battery quantity

2

Operating temperature - max

35 °C

Voltage

230V

Input cord length

1.5 m

Temperature range

0° to 35°C (32° to 95°F)

Ethernet interface

No

Communication

USB port (HID compliant)

Relative humidity

0-85% non-condensing

Output apparent power

1600 VA

Rack mounting kit

No

Output frequency

50/60 Hz

Runtime at full load

2 min

Type of interface

USB

Primary frequency - min

46 Hz

Battery rating

12 V / 9 Ah

Type

UPS

Output nominal voltage

230V default (220/230/240V)

Expansion slots

No

Input voltage range

165-285 V (adjustable to 150-285 V)

Nominal frequency

50/60 Hz

Primary frequency - max

70 Hz

Altitude

2000 m

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2023 Eaton. Tüm Hakları Saklıdır.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Eaton.com/socialmedia