Product data sheet

Specifications



APC Smart-UPS RT 48V Battery Pack

SURTA48XLBP

Overview

Lead time	Usually in Stock

Main

Number of rack unit	2U
Number of cables	1.0
Battery Type	Lead-Acid battery
Provided Equipment	Documentation CD User Manual

Batteries & Runtime

Battery blocks per string	4
Battery Slots Empty	0
Included Battery Modules	2
Device mounting	Enclosed battery cabinet
Battery Voltage	48V
RBC Quantity	2
Replacement battery	RBC57 SURTA48RMXLBP2U

Physical

Color	Black
Height	17.80 in (45.2 cm)
Width	3.39 in (8.6 cm)
Depth	22.01 in (55.9 cm)
Net Weight	72.55 lb(US) (32.91 kg)
Mounting Mode	Rack-mounted with kit

Environmental

Ambient Air Temperature for Operation	32…104 °F (0…40 °C)
Operating altitude	0...10000 ft

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Relative Humidity	0…95 % non-condensing
Ambient Air Temperature for Storage	-4…122 °F (-20…50 °C)
Storage altitude	0…50000 ft (0.00…15240.00 m)
Storage Relative Humidity	0…95 % non-condensing

Ordering and shipping details

GTIN	731304226352

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	10.00 in (25.4 cm)
Package 1 Width	28.74 in (73 cm)
Package 1 Length	24.02 in (61 cm)
Package 1 Weight	81.77 lb(US) (37.09 kg)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	REACh Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information
Take-back	Take-back program available

Contractual warranty

Warranty	2 years repair or replace

Recommended replacement(s)