Product data sheet
Characteristics

SMX120RMBP2U
APC Smart-UPS X 120V External Battery Pack Rack/Tower



Overview

Lead time	Usually Ships within 2 Weeks

General

Provided equipment	Installation guide Rack Mounting brackets

Physical

Number of rack unit	2U
Color	Black
Maximum Depth	26.26 in (66.7 cm)
Maximum Height	3.35 in (8.5 cm)
Net Weight	124.25 lb(US) (56.36 kg)
Maximum Width	17.01 in (43.2 cm)

Environmental

Ambient air temperature for operation	32…104 °F (0…40 °C)
Relative humidity	0…95 %
Operating altitude	0...10000 ft
Ambient air temperature for storage	5…113 °F (-15…45 °C)
Storage altitude	0…50000 ft (0.00…15240.00 m)

Batteries & Runtime

Battery blocks per string	10
Device mounting	Enclosed battery cartridge
Battery type	Lead-Acid battery
Included Battery Modules	0
Battery Slots Empty	0
RBC Quantity	2
Battery voltage	120 V

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein.
This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.
It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof.
Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Ordering and shipping details

Category	11309 - APC RESALE PRODUCTS
GTIN	00731304295839
Nbr. of units in pkg.	1
Package weight(Lbs)	1 lb(US) (0.45 kg)
Returnability	No

Packing Units

Package 1 Height	9.57 in (24.3 cm)
Package 1 width	23.46 in (59.6 cm)
Package 1 Length	34.21 in (86.9 cm)
Number of Units in Package 3	8

Offer Sustainability

Sustainable offer status	Green Premium product
REACh free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes

Contractual warranty

Warranty	2 years repair or replace